Vercelli Fire Fitting Instructions



It's important that before starting that you carefully read these instructions and the instructions supplied inside the appliance.

Note - the surfaces of your fireplace can be scratched or damaged if care is not taken during installation. A second pair of hands will be necessary to complete this installation safely and damage free. It is the installers responsibility to ensure that the appliance is securely anchored is securely fixed to the wall using appropriate fittings.

Ensure that you keep all screws that were removed for spare and future use.

Secure the appliance to the wall:

- 1. Carefully place the appliance on its back on the floor.
- On the bottom underside of the base, place the squared 'L' brackets towards the back of the suite, over one of the three pilot holes, so it is flush. One in the middle and two at either side, towards the edge. (Proceed to Fitting the Legs)
- 3. Once the legs and fire have been fitted, place the suite against the wall and secure from the bottom using the brackets previously attached to the suite. It is the installers responsibility to ensure that the appropriate fittings are used to fit to the wall.

Fitting the Legs:

- 1. Line up the legs with the trim from the front view of the fire and place over the pilot holes (Image D/E).
- 2. Screw in from front to back, one at a time to make sure that the legs are straight before securing with the rest of the screws. This ensures that the tension is distributed evenly for the legs (Image F).

Fitting the Fire:

- 1. Remove the screw that is marked in 'Image A)' on both sides of the electric fire.
- 2. Using the brackets provided, place them over the screw hole and fit the new bracket into the original place.
- 3. Once the brackets are fitted then the fire can be placed inside the surround.
- 4. Screw in the bracket to the timber work from behind to anchor the fire in place.

Image B)

Image C)







Image E)



Image F)





